



Safety data sheet

Colour Oil

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 17-09-2009/ LFH Replaces: 08-04-2008	Distributor: WoodCare Denmark A/S Tværvej 6 6640 Lunderskov
Product use: Surface treatment	Tel:99585600 Fax:99585634 Emergency telephone number: 99585600 The emergency telephone is open between 8 a.m. and 4 p.m. Contact person:Lene Funder Hein Email: info@ttwoodcare

2. Hazards identification

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Additional information Persons with a known allergy to cobalt bis(2-ethylhexanoate) may exhibit an allergic response to the product. Risk of self-ignition: Due to the risk of self-ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

3. Composition/information on ingredients

Einecs no.	CAS No.	Substances	Classification	w/w%	
205-250-6	136-52-7	cobalt bis(2-ethylhexanoate)	Xi;R38-R43	<0,3	-
245-018-1	22464-99-9	2-ethylhexanoic acid, zirconium salt	Xi;R38 N R50/53	<1	-
265-149-8	64742-47-8	Distillates (petroleum), hydrotreated light	Xn;R65	40-50	4
265-150-3	64742-48-9-a	Naphtha (petroleum), hydrotreated heavy	Xn;R65,R66	<2	4

4) R65 is not applicable due to the high viscosity of the product.
Please see section 16 for the full text of the R-phrases

4. First aid measures

Inhalation Seek fresh air.
Ingestion Wash out mouth thoroughly and drink 1-2 glasses of water in small sips.
Skin Wash skin with soap and water.
Eyes Rinse immediately with water (preferably using eye wash) for at least 5 minutes. Open eyes wide. Remove any contact lenses.
Other information When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

Prepared on: 17-09-2009/LFH
Replaces: 08-04-2008

Colour Oil

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water stream, as it may spread the fire. Use water or water mist to cool non-ignited stock. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

6. Accidental release measures

Smoking and naked flames prohibited. Use the same personal protective equipment as stated in section 8.

7. Handling and storage

Handling

See section 8 for information about precautions for use and personal protective equipment. Smoking and naked flames prohibited.

Storage

Store safely, out of reach of children and not together with food, animal feeding stuffs, medicines, etc.

8. Exposure controls/ personal protection

Precautions for use

Use the product under well-ventilated conditions.

Respiratory protection

Not required.

Gloves and protective clothing

Wear protective gloves made of nitrile rubber,

Eye protection

Wear safety goggles if there is a risk of eye splash.

Occupational exposure limits

Contains no substances subject to reporting requirements.

9. Physical and chemical properties

Appearance: Liquid

Flash point: -°C >100

Density: - g/mL 0,98-1,10

10. Stability and reactivity

The product is stable when used in accordance with the supplier's directions.

11. Toxicological information

Acute

Inhalation

Inhalation of vapours may cause irritation to the upper airways.

Ingestion

Ingestion may cause discomfort.

Skin contact

May cause slight irritation.

Eye contact

May cause eye irritation.

Risk of sensitization

The product contains small amounts of cobalt bis(2-ethylhexanoate). Persons with a known allergy may exhibit an allergic response to the product.

Long-term effects

None known.

12. Ecological information

Avoid discharge to drain or surface water.

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Collect spills and waste in closed and sealed containers and send to the local disposal facility for chemical waste.

14. Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

15. Regulatory information

Hazard designation:

R-phrases

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. (R52/53)

Other labelling

Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction. Risk of self-ignition: Due to the risk of self-ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

Volatile organic compounds (VOC):

This product contains a maximum of 60 g VOC/L. The limit value is 500 g VOC/L (cat. A/-)

Chemical safety assessment

Chemical safety assessment has not been performed.

Prepared on: 17-09-2009/LFH
Replaces: 08-04-2008

Colour Oil

16. Other information

Training requirement

No special training is required, but a thorough knowledge of this safety data sheet should be a prerequisite condition.

Sources used

Approved classification and labelling guide (fifth edition) 2002.

ikke oversat

Approved Supply List (seventh edition): Information approved for the classification and labelling of substances and preparations dangerous for supply. Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Other information

This safety data sheet was prepared from information provided by the supplier about the product at the time of preparation (e.g. data sheets and the like).

Full text of the R-phrases that are stated in section 3.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com (Made in Toxido®) UK