



Safety data sheet

Maintenance Paste

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 01-12-2008/ LFH	Distributor: WOODCARE DENMARK A/S Havnevej 17 9560 Hadsund
Product use: Surface treatment of wood.	Tel:99585600 Fax:99585634 Emergency telephone number: +45 99585600 The emergency telephone is open between 8 a.m. and 4 p.m. on workdays. Contact person:Simon Greve Email: info@ttwoodcare.com

2. Hazards identification

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition/information on ingredients

Einecs no.	CAS No.	Substances	Classification	w/w%	
265-150-3	64742-48-9-b	Naphtha (petroleum), hydrotreated heavy	R10 Xn;R65 R66	10-15	4
265-185-4	64742-82-1-c	Naphtha (petroleum), hydrodesulfurized heavy	R10 Xn;R65 R66 R67 N; R51/53	15-20	4
265-148-2	68551-20-2	Iso Alkaner	Xn, R65-66	1-5	4

4) R65 is not applicable due to the high viscosity of the product.
Please see section 16 for the full text of the R-phrases

4. First aid measures

Inhalation Seek fresh air. Seek medical advice in case of persistent discomfort.
Ingestion Rinse mouth thoroughly and then drink plenty of water. If vomiting occurs, keep head low so that stomach contents do not enter lungs. Seek medical advice if symptoms persist.
Skin Wash skin with soap and water.
Eyes Rinse immediately with water (preferably using eye wash) for at least 5 minutes. Open eyes wide. Remove any contact lenses.
Burns Rinse with water until pain stops. Remove clothes which do not adhere to the body - seek medical advice, if possible continue rinsing until doctor takes over treatment.
Other information When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water stream, as it may spread the fire. Use water or water mist to cool non-ignited stock. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

6. Accidental release measures

Prevent spillage from entering drains and/or surface water.

7. Handling and storage

Handling

See section 8 for information about precautions for use and personal protective equipment.

Storage

There are no special storage requirements but the product should be stored safely, out of reach of children and not together with food, animal feeding stuffs, medicines, etc.

8. Exposure controls/ personal protection

Precautions for use

Use the product under well-ventilated conditions.

Respiratory protection

Not required.

Gloves and protective clothing

Wear protective gloves made of nitrile rubber,

Eye protection

Wear safety goggles if there is a risk of eye splash.

Occupational exposure limits

Contains no substances subject to reporting requirements.

9. Physical and chemical properties

State: Paste

Flash point: -°C 70

Density: - g/ml 0,9

10. Stability and reactivity

The product is stable when used in accordance with the supplier's directions. Risk of self-ignition: Due to the risk of self-ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

11. Toxicological information

Acute

Inhalation

Inhalation of vapours may cause irritation to the upper airways.

Ingestion

Ingestion may cause discomfort.

Skin contact

Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

May cause eye irritation.

Long-term effects

None known.

12. Ecological information

Avoid discharge to drain or surface water.

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Collect spills and waste in closed and sealed containers and send to the local disposal facility for chemical waste.

14. Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

15. Regulatory information

Hazard designation:

R-phrases

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. (R52/53)

Other labelling

None.

Volatile organic compounds (VOC):

This product contains a maximum of 380 g VOC/L. The limit value is 600 g VOC/L (cat. A/-)

Chemical safety assessment

Chemical safety assessment has not been performed.

16. Other information

Training requirement

No special training is required, but a thorough knowledge of this safety data sheet should be a prerequisite condition.

Sources used

Other information

This safety data sheet was prepared from information provided by the supplier about physical/chemical properties and all ingredients in the product.

Full text of the R-phrases that are stated in section 3.

R10 Flammable.

R25 Toxic if swallowed.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.