



Safety data sheet

High Solid Master Oil

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 09-10-2009/ LFH
Replaces: 10-04-2008

Product use: Surface treatment

Distributor:

WoodCare Denmark A/S
Tværvej 6
6640 Lunderskov

Tel:99585600 Fax:99585634

Emergency telephone number: 99585600

The emergency telephone is open between 8 a.m. and 4 p.m.

Contact person:Lene Funder Hein

Email: info@ttwoodcare

2. Hazards identification

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Additional information

Persons with a known allergy to cobalt bis(2-ethylhexanoate) may exhibit an allergic response to the product.

Risk of self-ignition: Due to the risk of self- ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

3. Composition/information on ingredients

Einecs no.	CAS No.	Substances	Classification	w/w%
205-250-6	136-52-7	cobalt bis(2-ethylhexanoate)	Xi;R38-R43	<0,3 -
245-018-1	22464-99-9	2-ethylhexanoic acid, zirconium salt	Xi;R38 N R50/53	<1 -
265-149-8	64742-47-8	Distillates (petroleum), hydrotreated light	Xn;R65, R66	10-20 4
265-150-3	64742-48-9-a	Naphtha (petroleum), hydrotreated heavy	Xn;R65,R66	1-3 4

4) R65 is not applicable due to the high viscosity of the product.
Please see section 16 for the full text of the R-phrases

4. First aid measures

Inhalation

Seek fresh air.

Ingestion

Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. Seek medical advice if symptoms persist.

Skin

Wash the skin thoroughly with water and continue washing for a long time.

Eyes

Flush immediately with water (preferably using eye wash equipment) for at least 5 minutes. Open eye wide. Remove any contact lenses. Seek medical advice if symptoms persist.

Other information

When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water stream, as it may spread the fire. Use water or water mist to cool non-ignited stock. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

Prepared on: 09-10-2009/LFH
Replaces: 10-04-2008

High Solid Master Oil

6. Accidental release measures

Contain and absorb spill with sand, cat litter or other absorbent, non-combustible material and transfer to suitable waste containers. See section 13 for instructions on disposal. Smoking and naked flames prohibited. Use the same personal protective equipment as stated in section 8.

7. Handling and storage

Handling

See section 8 for information about precautions for use and personal protective equipment. Smoking and naked flames prohibited.

Storage

Store safely, out of reach of children and not together with food, animal feeding stuffs, medicines, etc.

8. Exposure controls/ personal protection

Precautions for use

Use the product under well-ventilated conditions.

Respiratory protection

Not required.

Gloves and protective clothing

Wear protective gloves made of nitrile rubber,

Eye protection

Wear safety goggles if there is a risk of eye splash.

Occupational exposure limits

Contains no substances subject to reporting requirements.

9. Physical and chemical properties

Appearance: Liquid

Flash point (°C):>100

Relative density (g/ml):0,93

Solubility in water (g/100 ml): Insoluble

10. Stability and reactivity

The product is stable when used in accordance with the supplier's directions.

11. Toxicological information

Acute

Inhalation

Inhalation of vapours may cause irritation to the upper airways.

Ingestion

Ingestion may cause discomfort.

Skin contact

May cause slight irritation.

Eye contact

May cause eye irritation.

Risk of sensitization

The product contains small quantities of cobalt bis(2-ethylhexanoate). Persons with stated allergy may react to the product.

Long-term effects

None known.

12. Ecological information

Avoid discharge to drain or surface water.

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Prepared on: 09-10-2009/LFH
Replaces: 10-04-2008

High Solid Master Oil

13. Disposal considerations

Collect spills and waste in closed and sealed containers and send to the local disposal facility for chemical waste.

14. Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

15. Regulatory information

Hazard designation:

R-phrases

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. (R52/53)

Other labelling

Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

Risk of self-ignition: Due to the risk of self-ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

Volatile organic compounds (VOC):

This product contains a maximum of 25 g VOC/L. The limit value is 500 g VOC/L (cat. A/i)

Chemical safety assessment

Chemical safety assessment has not been performed.

16. Other information

Training requirement

No special training is required, but a thorough knowledge of this safety data sheet should be a prerequisite condition.

Sources used

Approved classification and labelling guide (fifth edition) 2002.

Approved Supply List (seventh edition): Information approved for the classification and labelling of substances and preparations dangerous for supply. Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Other information

This safety data sheet was prepared from information provided by the supplier about physical/chemical properties and all ingredients in the product.

Full text of the R-phrases that are stated in section 3.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Amendments have been made in the following sections

2,3,15

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com (Made in Toxido®) UK